IN THE CLAIMS

Please amend claims 3, 12, 20 and 26.

1. **(previously canceled)**

2. **(previously canceled)**

3. **(currently amended)** A method for measuring an indication of attributes of materials containing a fluid state, the method comprising the steps of:
   a. providing a single time-domain signal indicative of attributes of said materials ~~in a single event measurement~~;
   b. constructing a time-domain averaged data train from said signal, the averaging being performed over two or more time intervals Δ_i, wherein at least two of said two or more time intervals Δ_i are different; and
   c. computing an indication of attributes of said materials from the time-domain averaged data train.

4. **(previously amended)** The method of claim 3 wherein the following expression is used to construct the time-domain averaged data train within a Δ_i time interval:

   $S_{\Delta_i} = \int_{t}^{t+\Delta_i} dt' S(t')/\Delta_i$, where $S(t)$ is the provided time-domain signal.

5. **(previously amended)** The method of claim 3, wherein a portion of the time-domain averaged data train is constructed at times $t = t_0, t_0 + \Delta_i, t_0 + 2\Delta_i, \ldots, t_0 + N\Delta_i$.

6. **(previously amended)** The method of claim 3, wherein the time-domain signal is an NMR echo train.

7. **(original)** The method of claim 6, wherein the step of computing an indication of attributes is performed using inversion of the constructed time-domain averaged data train into T_2 domain.

8. **(previously amended)** The method of claim 7, wherein the T_2 distribution is estimated using the following expression $S_{\Delta_i}(t) = \sum_{T_2} \phi(T_2)\exp(-t/T_2)(1-\exp(-\Delta_i/T_2)) + Noise$,

   where $\phi(T_2)$ is the porosity corresponding to the exponential decay time T_2.

9. **(previously amended)** The method of claim 3 further comprising the step of averaging two or more constructed time-domain averaged data trains to increase the signal-to-noise ratio (SNR) of the measurement.

10. **(previously canceled)**

11. **(previously canceled)**

12. **(currently amended)** A method for measuring an indication of attributes of materials containing a fluid state in a formation surrounding a borehole, comprising the steps of:
    a. providing ~~an~~ a single NMR echo-train indicative of attributes of materials ~~along the borehole~~ in the formation surrounding the borehole;
    b. constructing a single ~~event~~ time-domain averaged data train from said NMR echo train, the averaging being performed over two or more time intervals Δ_i, wherein at least two of said two or more time intervals Δ_i are different; and
    c. computing an indication of attributes of said materials from the time-domain averaged data train.

13. **(previously amended)** The method of claim 12 further comprising the step of averaging two or more constructed time-domain averaged data trains to increase the signal-to-noise ratio (SNR) of the measurement.

14. **(previously amended)** The method of claim 12 wherein the following expression is used to construct the time-domain averaged data train: $Echo_{\Delta_i}(t) = \int_t^{t+\Delta_i} dt' Echo(t')/\Delta_i$, where $Echo(t)$ is the provided time-domain signal over a time interval Δ_i.

15. **(previously amended)** The method of claim 12, wherein a portion of the time-domain averaged data train is constructed at times $t = t_0, t_0 + \Delta_i, t_0 + 2\Delta_i, \ldots, t_0 + N\Delta_i$.

16. **(original)** The method of claim 15, wherein the step of computing an indication of attributes is performed using inversion of the constructed time-domain averaged data train into T_2 domain.

17. **(previously amended)** The method of claim 16, wherein the T_2 distribution is estimated using the following expression

$Echo_{\Delta_i}(t) = \sum_{T_2} \phi(T_2)\exp(-t/T_2)(1-\exp(-\Delta_i/T_2)) + Noise$, where $\phi(T_2)$ is the porosity corresponding to the exponential decay time T_2.

18. (previously canceled)

19. (previously canceled)

20. (currently amended) A method for increasing the spatial resolution of NMR logging measurements, comprising the steps of:

a. providing ~~an~~ a single NMR echo-train indicative of attributes of materials of interest; and

b. constructing a single time-domain averaged data train from said single NMR echo train, the averaging being performed over two or more time intervals Δ_i, wherein at least two of said two or more time intervals Δ_i are different.

21. (previously amended) The method of claim 20 further comprising the step of averaging two or more constructed time-domain averaged data trains to increase the signal-to-noise ratio (SNR) of the measurement.

22. (previously amended) The method of claim 20 wherein the following expression is used to construct the time-domain averaged data train: $Echo_{\Delta_i}(t) = \int_t^{t+\Delta_i} dt' Echo(t')/\Delta_i$, where $Echo(t)$ is the provided time-domain signal.

23. (previously amended) The method of claim 20, wherein the time-domain averaged data train is constructed at times $t = t_0, t_0 + \Delta_i, t_0 + 2\Delta_i, \ldots, t_0 + N\Delta_i$.

24. (original) The method of claim 23, wherein the step of computing an indication of attributes is performed using inversion of the constructed time-domain averaged data train into T_2 domain.

25. (previously amended) The method of claim 24 wherein the T_2 distribution is estimated using the following expression

$Echo_{\Delta_i}(t) = \sum_{T_2} \phi(T_2)\exp(-t/T_2)(1-\exp(-\Delta_i/T_2)) + Noise$, where $\phi(T_2)$ is the porosity corresponding to the exponential decay time T_2.

26. (currently amended) A method for real-time processing of NMR logging signals, comprising the steps of:

a. providing real-time data corresponding to a ~~single event~~ single NMR echo-train indicative of physical properties of materials of interest;

b. constructing a time-domain averaged data train from said NMR echo train, the averaging being performed over variable time interval Δ using the expression $S_{\Delta}(t) = \int_{t}^{t+\Delta} dt' S(t')/\Delta$, where $S(t)$ is the provided measurement signal, and the time-domain averaged data train is constructed at times $t = t_0, t_0 + \Delta, t_0 + 2\Delta, \ldots, t_0 + N\Delta$; and

c. computing in real time an indication of the physical properties of said materials based on the constructed time-domain averaged data train.

27. (original) The method of claim 26, further comprising the step of: inverting of the constructed time-domain averaged data train into the T_2 domain, wherein the T_2 distribution is modeled using the expression $Echo_{\Delta}(t) = \sum_{T_2} \phi(T_2) \exp(-t/T_2)(1 - \exp(-\Delta/T_2)) + Noise$, where $\phi(T_2)$ is the porosity corresponding to the exponential decay time T_2.

28. (original) The method of claim 26, further comprising the step of averaging two or more constructed time-domain averaged data trains to increase the signal-to-noise ratio (SNR) of the measurement.